



ORCA
VALUE SOLUTION

RESILIENT TIRES

The Orca tire is developed with the latest technology. Quality compounds and a modern and highly functional design guarantee an attractive product with economical benefits:


- **long mileage**
- **low energy consumption**
- **excellent cut resistance**

- **NATURAL RUBBER**
- **GOOD RESISTANCE TO FATIGUE**
- **HIGH STABILITY
MAXIMUM SAFETY**
- **OPTIMAL GRIP
AND TRACTION**
- ** NON MARKING
COMPOUND IS
ALSO AVAILABLE**



ORCA

- **TRELLEBORG ENGINEERED**
- **PREMIUM COMPOUNDS**
- **HIGH RELIABILITY**
- **FOR USE IN INDUSTRIAL APPLICATIONS**



ORCA

Size	Rim Width	Profile	Loc			Static load	Load capacity (kg)				
				Max. width	O.D.		Counterbalanced lift trucks up to 25 km/h		Other vehicles		
							mm	mm	Load Wheel	Steering Wheel	6 km/h
4.00- 8	3.00D - 8	sl	✓	130	406	1.100	950	730	950	860	730
15x4½- 8	3.00D - 8	sl	✓	132	377	1.210	1.040	800	1.040	940	800
5.00- 8	3.00D - 8	sl	✓	143	458	1.645	1.415	1.090	1.415	1.285	1.090
16x6- 8	4.33R - 8	sl	✓	164	417	1.690	1.455	1.120	1.455	1.320	1.120
18x7- 8	4.33R - 8	sl	✓	187	453	2.490	2.145	1.650	2.145	1.950	1.650
140/55-9	4.00E - 9	sl	✓	147	375	1.360	1.170	900	1.170	1.060	900
6.00- 9	4.00E - 9	sl	✓	173	529	2.190	1.885	1.450	1.885	1.710	1.450
21x8- 9	6.00E - 9	sl	✓	216	524	3.200	2.755	2.120	2.755	2.505	2.120
6.50-10	5.00F - 10	sl	✓	191	576	2.720	2.340	1.800	2.340	2.185	1.800
200/50-10	6.50F - 10	sl	✓	221	458	2.870	2.470	1.900	2.470	2.240	1.900
23x9-10	6.50F - 10	sl	✓	243	583	4.000	3.445	2.650	3.445	3.125	2.650
7.00-12	5.00S - 12	sl	✓	207	657	3.380	2.920	2.240	2.920	2.640	2.240
23x10-12	8.00G - 12	sl	✓	275	583	4.380	3.770	2.900	3.770	3.420	2.900
27x10-12	8.00G - 12	sl	✓	275	676	4.530	3.900	3.000	3.900	3.540	3.000
7.00-15	5.50 - 15	sl	✓	213	731	4.115	3.545	2.725	3.545	3.215	2.725
7.50-15	6.50 - 15	sl	✓	229	757	4.530	3.900	3.000	3.900	3.540	3.000
28x9-15 (8.15-15)	7.00 - 15	sl	✓	233	693	4.530	3.900	3.000	3.900	3.540	3.000
250-15	7.00 - 15	sl	✓	265	720	5.510	4.745	3.650	4.745	4.300	3.650
	7.50 - 15	sl	✓	265	720	5.510	4.745	3.650	4.745	4.300	3.650
8.25-15	6.50 - 15	sl	✓	253	819	5.510	4.750	3.650	4.750	4.300	3.650
300-15	8.00 - 15	sl	✓	324	823	6.795	5.850	4.500	5.850	5.310	4.500
355/65-15	9.75 - 15	sl	✓	372	826	9.060	7.800	6.000	7.800	6.430	6.000

The above load capacities are based on available E.T.R.T.O. specifications for load and steering wheels on counterbalanced forklift trucks.